



PRODUCT ORDERING GUIDE

Tac Series LS

Custom products are available.

Contact sales@edriveactuators.com with your requirements.

BASE NUMBER		OPTIONS				SPECIAL													
L	S																		
Base No. (Capacity)		Unit Mounting Option				Motor Position				Custom Length (in)									
LS204 (400 lbf)		MB: Bottom Mount				1, 2, 3, 4				00.00									
LS209 (900 lbf)		MF: Foot Mount				0 = In-Line				N.C. Switch Qty									
LS305 (500 lbf)		CR: Rear Clevis**								0, 1, 2, 3, etc.									
LS310 (1,000 lbf)		FF: Front Flange**								N.O. Switch Qty									
LS320 (2,000 lbf)		TF: Front Trunnion**				Gearbelt Reduction				0, 1, 2, 3, etc.									
Std. Stroke Length*		Rod End Option				00: In-Line/Direct Coupled													
24: 24 in.		E: Female Eye				10: 1:1													
30: 30 in.		F: Female Thread				20: 2:1													
36: 36 in.		A: Self-Aligning Coupler				Switch Type													
42: 42 in.		M: Male Thread				A: Hall Sourcing PNP													
48: 48 in.		S: Spherical Rod Eye				B: Hall Sinking NPN													
54: 54 in.		Configuration				C: Reed													
60: 60 in.		L: In-Line				X: No Switches													
		U: Parallel Offset																	

* LS204 – LS209 are available with stroke lengths up to 36 in.
 LS305 – LS320 are available with stroke lengths from 30 in. to 60 in.
 ** Vertical Mounting Only